


INSTALLING STUCCO, STONE, OR MASONRY?

OMEGA'S **ABCS** LINE has the SOLUTION.

DETERMINE WHICH PRODUCTS ARE BEST FOR YOUR NEEDS

PROJECT NEED(S)	TYPE OF PROJECT BEING APPLIED		
	STUCCO	STONE	MASONRY
Improve bond strength	BOND-CRETE POLYLOC AKROLOC	BOND-CRETE POLYLOC AKROLOC	BOND-CRETE POLYLOC AKROLOC
Seal surface to protect from water or staining	OMEGASEAL 1000 OMEGAGUARD¹ OMEGAGUARD PLUS¹ AQUASHIELD	OMEGASEAL 1000 OMEGAGUARD¹ OMEGAGUARD PLUS¹	OMEGASEAL 1000 OMEGAGUARD¹ OMEGAGUARD PLUS¹
Increase tensile or flexural strength	POLYLOC AKROLOC	POLYLOC AKROLOC	POLYLOC AKROLOC
Clean surface	STUCCO CLEANER	STUCCO CLEANER	STUCCO CLEANER
Prevent efflorescence (white stains on surface)	E-FX ADMIX	AQUASHIELD	AQUASHIELD
Accelerate curing time/Cold weather application	OMEGACURE	OMEGACURE	OMEGACURE

¹ Surface must be porous



STUCCO & MASONRY SOLUTIONS

Product Selection Guide



A
ADMIXES

To improve the performance of cement-based products

B
BONDERS

To adhere new cement products to existing substrates

C
CLEANERS

To clean and maintain the appearance of surfaces

S
SEALERS

To protect surfaces from the elements and staining



OCTOBER 2011

OMEGA PRODUCTS INTERNATIONAL, INC.
1681 CALIFORNIA AVE • CORONA, CA 92881
P 800.600.6634 • F 951.520.2594
WWW.OMEGA-PRODUCTS.COM



ADMIXTURES

Admixtures are used in cement-based products to improve the performance of various properties.

Use these admixes to reduce cracking and increase tensile, bond, and flexural strengths of the approved products listed below.

	POLYLOC	AKROLOC	ADMIX 500
TECHNOLOGY	PVA	100% Acrylic	100% Acrylic
AREA OF USE	<i>Cement-based products:</i> <ul style="list-style-type: none"> • Stucco • Concrete • Mortar • Sand/cement slurry coat <i>Gypsum-based products</i>	<i>Cement-based products:</i> <ul style="list-style-type: none"> • Stucco • Concrete • Mortar • Sand/cement slurry coat 	<ul style="list-style-type: none"> • Stucco • Concrete • Mortar • Sand/cement slurry coat
OTHER FEATURES		Concentrated	Easy 1:1 admix to water ratio for most products
PACKAGING	1-gal bottles 5-gal pails	1-gal bottles 5-gal pails	1-gal bottles 5-gal pails

Additional products to increase the performance of cement-based materials.

	OMEGACURE	E-FX ADMIX	AQUASHIELD
DESCRIPTION	Accelerator to improve curing	Efflorescence reducing admix for cement-based products	Water repellent admix for stucco
AREA OF USE	<ul style="list-style-type: none"> • One coat stucco • Scratch and brown coat • Cement-based finish coats • Cement plasters • Other approved cementitious products 	<ul style="list-style-type: none"> • Cement-based finishes • Cement-based fog coat 	<ul style="list-style-type: none"> • ColorTek Stucco • Other cement-based products
OTHER FEATURES	<ul style="list-style-type: none"> • Accelerates the cement hydration • Allows cold weather applications • Increases early strength and hardness • Non-corrosive 	<ul style="list-style-type: none"> • Reduces efflorescence • Retains natural appearance 	<ul style="list-style-type: none"> • Increase water-resistance • Improves freeze/thaw resistance • Retains natural appearance • No extra application step(s)
PACKAGING	1-gal bottles 5-gal pails	4-oz bottles	1-lb packages

BONDERS

Bonders are used to adhere new concrete, portland cement plaster, mortars, other cementitious products, and gypsum plaster mixes to structurally sound substrates.

	BOND-CRETE	POLYLOC	AKROLOC
TECHNOLOGY	PVA	PVA	100% Acrylic
AREA OF USE	<i>Cement-based products:</i> <ul style="list-style-type: none"> • Stucco • Concrete • Mortar • Sand/cement slurry coat <i>Gypsum-based products</i>	<i>Cement-based products:</i> <ul style="list-style-type: none"> • Stucco • Concrete • Mortar • Sand/cement slurry coat <i>Gypsum-based products</i>	<i>Cement-based products:</i> <ul style="list-style-type: none"> • Stucco • Concrete • Mortar • Sand/cement slurry coat
COLOR	Gold colored for coverage indication	White liquid, dries clear	White liquid, dries clear
APPLICATION	Apply up to 10 days prior to the material to be bonded	Apply up to 10 days prior to the material to be bonded	Apply bonding material while AkroLoc is still tacky. Cannot dry.
RE-EMULSIFYING	Yes	Yes	No
STANDARDS	ASTM C932		
COVERAGE	200ft ² to 300ft ²	200ft ² to 300ft ²	100ft ² to 400ft ²
PACKAGING	1-gal bottles 5-gal pails	1-gal bottles 5-gal pails	1-gal bottles 5-gal pails



CLEANERS

Cleaners are used to clean and maintain the appearance of surfaces.

	STUCCO CLEANER
DESCRIPTION	Concentrated cleaner for stucco and other cement surfaces
AREA OF USE	• Stucco • Concrete • CMU • Siding
COLOR/SMELL	Red/citrus
COVERAGE	Up to 1,000ft ² per 32-oz., 4,000ft ² per 1-gal.
PACKAGING	32-oz spray bottle, 1-gal bottles

SEALERS

Sealers are used over approved surfaces to increase weatherability, provide moisture protection, and resist staining while protecting the substrate against freeze thaw cycles and allowing for easy maintenance.

	OMEGAGUARD	OMEGAGUARD PLUS	OMEGASEAL 1000
TECHNOLOGY	Silicon-based sealer	Silane/Siloxane sealer	Acrylic-based sealer
AREA OF USE	Porous materials such as stucco, masonry, or stone	Vertical or horizontal, porous materials such as stucco, masonry, stone, or cement	Cement-based materials, stone, acrylic /painted surfaces
METHOD OF SEALING	Penetrates into the surface pores	Penetrates into the surface pores	Creates continuous protective film on surface
APPEARANCE	Natural	Natural	Slight sheen
STAIN RESISTANCE	Water-based stains	Water-based stains Some oil-based stains	Water-based stains Oil-based stains
CAN BE PAINTED AFTER APPLICATION?	No	Yes	Yes
COVERAGE	100ft ² to 300ft ²	100ft ² to 200ft ²	150ft ² to 250ft ²
PACKAGING	1-gal bottles 5-gal pails	1-gal bottles 5-gal pails	1-gal bottles 5-gal pails