

MATERIAL SAFETY DATA SHEET

Omega Products International, Inc.
1681 California Ave, Corona CA 92881
Emergency Phone: 951-737-7447 or 800-600-6634

May 2010

Section I: Product Identification

Trade Name: Omega AkroLoc (Acrylic Bonder), Omega Admix 500, Diamond Wall PM Admix
Chemical Name: None
Chemical Family: Mixture

Section II: Component Information

<u>Component</u>	<u>PCT</u>	<u>ACGIH TLV</u>	<u>(OSHA PEL)</u>	<u>CAS #</u>
Acrylic Polymer	10-45			Nonhazardous
Residual Monomers	<0.1	Not Required		Not Required

Section III: Physical Data:

Appearance and Odor:	Thin, watery liquid with a mild ammonia odor.
Boiling Point:	100°C/212 °F.
Melting Point:	N/A
Vapor Pressure:	N\A
Vapor Density:	<1
Specific Gravity:	>1
Solubility:	Dilutable
Evaporation Rate:	<1, water

Section IV: Fire and Explosion Data:

Flash Point:	Noncombustible
Lower Explosion Limit:	N/A
Auto-ignition Temp:	N/A
Unusual Hazards:	Material can splatter above 100°C/212°F. Polymer film can burn
Extinguishing Media:	Use Extinguishing media appropriate to surrounding fire.
Personal Protection:	Wear self-contained breathing apparatus(pressure demand MSHA/NIOSH approved or equivalent) and full protective gear.

Section V: Health Hazard Data

ACGIH TLV (OSHA PEL):	Mixture (See section II)
Primary Routes of Exposure:	Inhalation, Skin and Eye Contact.
Inhalation:	Inhalation of dust from sanding can cause headache, nausea, irritation of nose, throat or lungs.
Eye Contact:	Direct contact with eyes can cause a slight eye irritation.
Skin Contact:	Prolonged or repeated skin contact can cause a slight skin irritation.
First Aid Procedure:	
Inhalation:	Move subject to fresh air.
Eye Contact:	Flush eyes with running water for at least 15 minutes. Consult a physician if irritation persists.
Skin Contact:	Wash affected area thoroughly with soap and water. Consult a physician if irritation persists.
Ingestion:	If swallowed, give at least 2 glasses of water to drink, consult a physician. Never give anything by mouth to an unconscious person.

Carcinogenicity: IARC: Not Regulated NTP: Not Regulated OSHA:Not Regulated

MATERIAL SAFETY DATA SHEET

Omega Products International, Inc.
1681 California Ave, Corona CA 92881
Emergency Phone: 951-737-7447 or 800-600-6634

May 2010

Section VI: Reactivity Data

Stability: Stable. Avoid temperatures above 177°C/350°F., the onset of polymer decomposition. Thermal decomposition is dependent on time and temperature.

Incompatibility: No known incompatible materials.

Hazardous Decomposition: Thermal decomposition may yield acrylic monomers.

Hazardous Polymerization: Will not occur.

Section VII: Spill or Leak Procedures

Personal Protection: See section V Health Hazard Data and Section VII Special Protection.

Procedures: Keep spectators away. Floor may be slippery. Use care to avoid falling. Immediately with inert materials (e.g. sand, earth). Transfer liquids and solid diking material to suitable containers for recovery or disposal.

Waste Disposal: Dispose of in accordance with applicable Federal, State and Local regulations. Keep spills and runoff out of municipal sewers and open bodies of water.

Section VIII: Special Protection Information

Respiratory Protection: None required for normal use of this product. If material is sanded or ground when dry, NIOSH/MSHA approved respirators for dust should be provided and used. As with any safety product, workers using respirators should be trained in the proper selection, use and care of such equipment.

Eye Protection: Use chemical splash goggles (ANSI 287.1 or approved equivalent).

Hand Protection: Rubber or plastic gloves.

Other Protective equipment: Local ventilation, if needed. Full flow eyewash station.

Section IX: Special Precautions and Information

US DOT Hazard Class: Not Regulated.

NTP: Health 0 Flammability 0 Reactivity 0

HMIS: Health 0 Flammability 0 Reactivity 0 Protective Equipment E
(Health rating applies only to acute effects as defined by the National Paint and Coatings Association.)

May contain trace amounts of formaldehyde, an animal carcinogen. Objective data indicates that the TWA of 0.5mg/m³ will not be exceeded under normal usage.

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Omega Product International, Inc's knowledge or is obtained from sources believed to be accurate. Omega Products International, Inc. does not assume any legal responsibility for its use or reliance upon same. Customers are encouraged to conduct their own tests. Before using any product, read its label.