



# Interior 2N1 Patch

A Gypsum-based, Patching Material



## Product Description

**Interior 2N1 Patch** is a fast setting, gypsum-based product that is manufactured from high-grade materials, and is ideal for limiting the time spent in patching cracks or other damage that may occur in interior walls and/or finishes.

## Features

- Premixed
- Quick Setting

## Benefits

- Requires only water at the job site
- Minimal patch time and shrinkage

## Basic Uses

Interior 2N1 Patch is designed for use as a patching material for the up keep and maintenance of interior walls and finishes.

## Area of Use

Interior 2n1 Patch may be applied to the following substrates:

1. Interior plaster
2. Drywall/gypsum sheathing

## Coverage

Approximately 15ft<sup>2</sup> (1.4m<sup>2</sup>), at 1/2" (12.7mm) thickness, per bag. Coverage will vary due to surface conditions and porosity along with surface temperatures. Ambient air conditions will also affect coverage amounts.

## Packaging

Moisture resistive, 25lb (11.34kg) bags

## Storage

1. Store bags in a cool, dry location.
2. Do not store in direct contact with the ground and/or concrete.
3. Store out of direct sunlight.
4. Protect bags from weather and other damage.

## Shelf Life

1 year

## Color

Natural white color

# Application Instructions



INTERIOR 2N1 PATCH

## Surface Preparation

All surfaces to receive application must be clean and free of debris, dirt, dust, talc, efflorescence, grease, oils, curing agents, and cleaning solutions. All drywall joints should be taped using fiber mesh tape and Interior 2N1 Patch. This will prevent possible delamination caused by rewetting of standard drywall tape compound.

## Mixing

1. Add 1.5 to 2 gallons (5.7L to 7.6L) of clean, potable water to a clean bucket or wheelbarrow for every 25lb bag of Interior 2N1 Patch.
2. Add Interior 2N1 Patch to the water.
3. Mix for 2 to 3 minutes with a Jiffler-type mixer or a hoe.

## Application

1. Apply Interior 2N1 by applying pressure forcing the material into all areas to be patched. Apply the material to a thickness that is higher than that of the existing surface.
2. Rod or screed the material even with the existing surface.
3. Allow the material to set and either water trowel smooth or texture to the desired appearance.
4. Allow Interior 2N1 Patch to dry completely.
5. Finish as required to match the color of the existing surface.

**WARNING:** Interior 2N1 Patch is a fast setting material, therefore it is recommended that the material be applied as quickly as possible.

## Drying

Drying time may vary due to ambient temperature, surface temperature, surface porosity, application methods, and/or depth of patch.

## Limitations

**DO NOT** apply product when the ambient and surface temperature is below 40°F (4°C). The ambient and surface temperature must stay consistently above this temperature for a minimum of 24 hours at 70°F (21°C) 55% R.H. (see DRYING). Material that is allowed to freeze may suffer irreparable damage. Protect all work from inclement weather with an approved protective system.

**DO NOT** add any other materials to the mixture of the product without written approval from Omega Products International, Inc.

**DO NOT** deviate in the mixing or application procedures contained in this, or any other Omega Product Data Sheet, without written approval from Omega Products International, Inc.

**DO NOT** apply Interior 2N1 Patch if there are contaminants on the receiving surface. Contaminates may include, but are not limited to, dust, debris, efflorescence, and/or oils.

**DO NOT** add any more water than prescribed.

**DO NOT** use excessive amounts of water when floating and/or troweling the texture.

**NOTE:** Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

## Cleaning

Cleaning may be accomplished with water immediately after use.

## Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

**KEEP OUT OF REACH OF CHILDREN**

www.omega-products.com

### Disclaimer

Omega Products International, Inc. [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond

the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

### Claims

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.

### Technical Assistance

Technical assistance and information is available by calling Omega Products International, Inc. at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at [info@omega-products.com](mailto:info@omega-products.com).

### Warranty

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.