



Coverage

Approximately 200ft² (18.5m²) per gallon, per coat. Coverage may vary due to ambient temperature, surface temperature, surface porosity, and/or application methods.

Packaging

1-gallon (3.8L) pre-mixed only
5-gallon (18.9L)

Storage

1. Store pails in a cool, dry location.
2. Store at a temperature between 40°F (4°C) and 90°F (32°C).
3. Store out of direct sunlight.
4. Protect pails from weather and other damage.

Shelf Life

2 years

Color

1-gallon: Pre-mixed with color.
5-gallon: Packaged clear and may be colored using AkroTique Color Bottles.

Product Description

A kroTique is a pigmented acrylic sealer designed to create a rustic, mottled finish similar to the timeless beauty of century old plaster. AkroTique offers an “Old World” look that does not take a lifetime to create. AkroTique also can be used without color as a sealer.

Features

Integral Color

Weather Resistant

Sealer

UV Stable

Low Gloss Finish

Easy to Clean

Vapor Permeable

Easy to Use

VOC Compliant

Benefits

Lasting, uniform color that resists fading or discoloration; UV resistant

Increases substrate weatherability, provides moisture protection, and resists staining

Seals and protects substrate against freeze thaw cycles; allows for easy maintenance

Non-yellowing

Clear with slight sheen on applied surfaces

Resists dirt accumulation and may be rinsed clean with water


Allows wall to naturally breath which aids drying and helps to prevent

Applied using a brush, roller, or sprayer and cleans up with water


Less than 26 g/L



Cigar #1



Sunset #158



California Gold #8

Basic Uses

AkroTique is used as an antique stain and/or sealer over acrylic-based, lime-based or cement-based finishes.

Area of Use

AkroTique may be applied to the following finishes:

1. AkroFlex and OmegaFlex Finishes.
2. ColorTek stucco and other approved cementitious substrates
3. Poured-in-place and/or Tilt-up concrete
4. Properly prepared interior/exterior painted surfaces
5. Valentino lime-based finishes

See appropriate finish product data sheet for more information.

NOTE: For additional colors see the AkroTique Color Collection, contact Omega Products, or visit www.omega-products.com.

Surface Preparation

All surfaces to receive application must be clean and free of loose debris, dirt and dust, efflorescence, grease, oils, curing agents, and cleaning solutions. Protect adjacent surfaces from unintentional application of AkroTique. Cement-based surfaces must be properly cured.

WARNING: Ensure that consistent wall temperatures are maintained prior to and during the application of AkroTique. Failure to do so will result in unwanted discoloration. This may include, but is not limited to, shadowing from landscaping, scaffolding, roof overhangs, etc.

Mixing

AkroTique must be field mixed immediately prior to application using a Jiffler-type mixer. Product must be continuously agitated throughout application. Do not allow AkroTique to settle.

1. Pour contents of AkroTique Color Bottle into the AkroTique pail.
2. Fill bottle with 2fl. oz. of clean, potable water. Re-cap and shake thoroughly. Pour the contents of the bottle into the pail.
3. Mix pail

Application

AkroTique may be applied with a roller, brush, sponge, Hudson-type sprayer, airless spray equipment and/or any combination of these tools depending on the desired results. See the Omega Technical Bulletin OP815 AkroTique Application Guide for complete application instructions.

Application as an antique stain and sealer

Job site mock-ups are highly recommend and should represent the actual job site application techniques.

1. Ensure that the receiving surface has been properly prepared according to the Surface Preparation section of this product data sheet.
2. Apply AkroTique in light, even coats.
3. If sagging or running occurs use a brush, sponge or roller to correct immediately.
4. Check wall throughout the application to ensure that uniformity and the desired appearance is achieved.

Application as a clear sealer

1. Mix thoroughly immediately prior to usage.
2. Insure the surface is clean and properly prepared.
3. Saturate the substrate with the sealer using the desired application method.

WARNING:

1. This product is not intended to create a uniform color appearance and therefore, Omega Products accepts no liability for any discoloration due to the use of this product. An accurate record of color quantities is highly recommended.
2. A jobsite mock-up wall is highly recommended to help insure that the desired color and appearance is obtained.

Drying

Drying time may vary due to climatic conditions, but should not take less than 24 hours at an ambient and surface temperature of 70°F (21°C) and 55% R.H. Variations in ambient and surface temperature and humidity may prolong drying time. All freshly applied material must be protected by an approved protective system from inclement weather until fully dry. It is the responsibility of the applicator to determine if the product is fully dry prior to exposing it to rain, snow, dew, and/or any other inclement weather condition that may be detrimental to the product.

Limitations

DO NOT apply product when the ambient and surface temperature is below 40°F (4°C). Material that is allowed to freeze may suffer irreparable damage. Protect all work from inclement weather with an approved protective system until fully dry.

DO NOT add any other materials to the mixture of the product without written approval from Omega Products International, Inc.

DO NOT deviate in the mixing or application procedures contained in this, or any other Omega product data sheets, without written approval from Omega Products International, Inc.

DO NOT apply AkroTique if there are contaminants on the receiving surface. Contaminates may include, but are not limited to dust, debris, efflorescence, and/or oils.

DO NOT use a Jiffler-type mixer that exceeds 500 RPM.

DO NOT apply AkroTique to a wet surface.

DO NOT apply AkroTique to plastered surfaces that have not been properly cured. Allow all surfaces to cure properly prior to application.

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

Due to job conditions beyond the control of Omega Products International, Inc. we make no warranty as to the acceptance of the final color. The actual integrally colored finish should be applied on a sample section of the project and verified for color accuracy prior to the actual application process.

Cleaning

Cleaning may be accomplished with water immediately after use.

Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

www.omega-products.com

Disclaimer

Omega Products International, Inc. [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond

the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

Claims

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.

Technical Assistance

Technical assistance and information is available by calling Omega Products International, Inc. at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at info@omega-products.com.

Warranty

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.